

ADSL


UM MODEL NO.:	SPECIFICATIONS	REV.	
UT20366S	ADSL Transformer	C1	2005/18

Electrical specification at 25°C:

- 1.) Turns Ratio and Polarity : 1CS : 1CS \pm 2% , Line side to Chip side.
- 2.) D.C.R. : 0.800 Ω max., PIN(8-6) .
: 0.800 Ω max., PIN(7-5) .
: 0.600 Ω max., PIN(1-3) .
: 0.800 Ω max., PIN(2-4) .
- 3.) Inductance : 176uH \pm 8% , at 10KHz 100mV, PIN(1-4); PIN(3-2) shorted.
- 4.) Leakage Inductance : 3.0uH max. ,at 100KHz 100mV, PIN(1-4) ; PIN(2-3)&PIN(8-6-7-5) shorted.
- 5.) Interwinding Capacitance : 50pF max. , at 100KHz 100mV ; PIN(1-3-2-4) to PIN(8-6-7-5)
- 6.) T.H.D. : -70.0dB max. ,at 10KHz 0.9V .
- 7.) HI-pot test : 1500Vac 60s or 1875Vac 1s , Line side to Chip side .

Note: The SIDB series transformer meets the specifications for supplementary insulation per UL60950-1, CSA60950-1, EN60950-1, IEC60950-1 with working voltage of 250V.

Schematic diagram & Dimension:



NOTE: 1. Packaging Information-Tape And Reel According To Item No. "AHT9L" of Data Sheet 01-00
2. Patent Pending Core Type (USA and Foreign)

UNIT : mm

Tolerances : \pm 0.2mm

AGENCY APPROVALS

UL60950-1	: FILE NO. E212730	IEC60950-1	: CB Rrf. #DK-8600
CSA 60950-1 (via C-UL)	: FILE NO. E212730	Nordic, Japan, & Australia Deviations	: CB Rrf. #DK-8600
Nemko (EN60950-1)	: Certificate NO. P05203901		



UNIVERSAL MICROELECTRONICS CO.,LTD.
TEL:886-4-23590096 FAX:886-4-23590129
<http://www.umec-web.com> Email:business@umec.com.tw

3,27TH RD.,TAICHUNG INDUSTRIAL PARK,
TAICHUNG,TAIWAN,R.O.C

E10-033-C