

DATA SHEET





UM MODEL NO.: UT23014	SPECIFICATIONS	REV.	1/1
	DUAL T1/E1 TRANSFORMERS FOR INFINEON #FALC IC APPLICATIONS	B0	05/26

Electrical Specifications at 25 °C :




- Turns Ratio : 1CT:2.4CT±2% @ 15.75KHz 1Vrms.PIN(1-2-3):(16-15-14)
1CT:1CT±2% @ 15.75KHz 1Vrms.PIN(6-7-8):(11-10-9)
- Pri. Inductance : 1.5mH Typ. @ 100KHz 20mVrms.
- Interwinding Capacitance : 35pF Max. @ 100KHz 1Vrms.
- Pri. Leakage Inductance : 0.5uH Max. @ 100KHz 1Vrms.
- Pri. DCR : 0.8Ω Max.
- Hi-Pot : 1500Vrms/2sec. Leakage Current 0.5mA Max. Pri. to Sec.
- Crosstalk : -65dB Typ. @ 0.5~5MHz
- Pri. Pins : 1-3 , 6-8
- Operating Temperature : -40°C TO +85°C

Dimensions & Schematics:

Non-RoHS:



RoHS compliant:



Coplanarity:0.1mm Tolerance:±0.25mm



NOTE : 1. Packaging Information:

- Non-RoHS : Tape and Reel according to Item NO.“SO16 ” of data sheet 01-00
 - RoHS compliant: Tape and Reel according to Item NO.“SO16A ” of data sheet 01-00
2. For RoHS compliant products:
- The UMEC ordering code: TG-UT23014
 - Date Code suffix to “G” for Green Product(XXXXG).
 - Solder : Sn/Ag/Cu .
3. Specifications are subject to change without prior notice.

E10-007-C



UNIVERSAL MICROELECTRONICS CO.,LTD.
TEL:886-4-23590096 FAX:886-4-23590129
http://www.umec-web.com Email:business@umec.com.tw

3,27TH RD.,TAICHUNG INDUSTRIAL PARK,
TAICHUNG,TAIWAN,R.O.C