


ISDN

| UM MODEL NO.: | SPECIFICATION | REV. | |
|---------------|----------------------------------|------|-------|
| UT28611 | S _O -Interface Module | A1 | 99/05 |

Characteristic data:

$R_I=R_{II} \approx 1.2\Omega$
 $R_{III} \approx 5.0\Omega$
 $R_{IV} \sim R_{VII} \approx 1.1\Omega$
 $T_u(\text{amb}) \leq 60^\circ\text{C}$


Schematic diagram:



Electrical Specification at 25⁰C:

- 1.) $L_{I+II} \geq 22\text{mH}$, (NI+II series), at 10KHz 100mV (core 1,2)
- 2.) Polarity and turns ratio tolerance: $\pm 2\%$ (core 1,2)
- 3.) Polarity and turns ratio tolerance: $\pm 1\%$ (core 3)
- 4.) $C_k \leq 105\text{pF}$, (NIII to NI+NIV || NII+V, or NI+VI || NII+VII), at 10KHz 100mV (core 1,2)
- 5.) $L_s I+II \leq 4.0\mu\text{H}$, (NI+II series, NIII shorted), at 100KHz 100mV (core 1,2)
- 6.) $L_{IV}=L_V=L_{VI}=L_{VII} \geq 3.6\text{mH}$, at 10KHz 100mV (core 3)
- 7.) HI-pot test:
 $U_p = 0.5\text{KV}_{\text{rms}}, 2\text{s}$ [NI/II (core 1)+NIV/V (core 3)+NIII (core 2) to NI/II (core 2) +NVI/VII (core 3)+NIII (core 1)]

Dimension:



NOTE: Specifications are subject to change without prior notice.

UNIT: mm

Tolerances: $\pm 0.2\text{mm}$



UNIVERSAL MICROELECTRONICS CO.,LTD.
 TEL:886-4-23590096 FAX:886-4-23590129
<http://www.umec-web.com> E-mail:business@umec.com.tw

3,27TH RD.,TAICHUNG INDUSTRIAL PARK,
 TAICHUNG,TAIWAN,R.O.C

E10-013-C