



DATA SHEET

UM PART NO.:	SPECIFICATION	REV.	
UT34350	COMMON MODE CHOKE	A0	03/28



ELELCTRICAL SPECIFICATION AT 25 °C :

1. INDUCTANCE : 1.170mH±25% AT 10KHz , 100mV , Ls , PIN(1-2) , (3-4).
2. D.C.Resistance : 200mΩ MAX. PIN(1-2) , (3-4)
3. TURNS RATIO & PHASE: 1:1 AT 15.75KHz , 1V , PIN(1-2):(3-4).
4. DIELECTRIC STRENGTH : 500Vrms/0.5mA/60Hz/2Sec. PIN1 TO PIN3.
5. RATED CURRENT(FOR 55⁰C RISE) : 1.22 Amps.

DIMENSION & SCHEMATIC :



SUGGESTED PCB LAYOUT



NOTE : specifications are subject to change without prior notice

UNIT : mm

E10-007-B



UNIVERSAL MICROELECTRONICS CO.,LTD.
 TEL:886-4-23590096 FAX:886-4-23590129
<http://www.umec-web.com> E-mail:business@umec.com.tw

3,27TH RD.,TAICHUNG INDUSTRIAL PARK,
 TAICHUNG,TAIWAN,R.O.C